



Providing redundancy for your project, the **SAVI Backup Server** mirrors every setting from **SAVI Server Pro** – making it ready for manual failover at any time. With over a decade of proven reliability, power, and performance, you can be confident that SAVI iQ will keep your project running even if things go wrong.

KEY BENEFITS

- All the features, power, and reliability of **SAVI Server Pro**, providing live backup for quick and easy replacement
- Fits into a single slot of our modular, 3-slot 1U chassis
- Front panel power reset button for easy access
- Includes the first year of Annual Support and Maintenance (ASM)

SPECIFICATIONS

Control, Monitoring, and Network	
Control	Ethernet connection, (2) USB 3.0, (1) USB-C
Network connectivity	10/100/1000 Mbps Ethernet
LAN port	8-pin RJ45 port with status LEDs
Processor/CPU	Intel® Core™ i5-10210U Processor (6 M Cache, up to 4.20 GHz)
RAM	16 GB DDR4
Storage	250 GB SSD
User Interface	Browser based UI

Electrical

Connection	Switching power supply AC/DC adapter, operation from 100 VAC +/-15% 2.1 mm power plug
Power consumption	90 W
Power input	100-240 V ~ 50/60 Hz input to include AC/DC power supply

Mechanical/Environmental

Dimensions	1.625 in x 4.75 in x 5.25 in (HxWxD)
Mounting	Fits into one slot of our 3-slot chassis, (2) screw taps for a secure fit
Operating temperature	32 to 122 °F (0 to 50 °C)
Storage temperature	-40 to 140 °F (-40 to 60 °C)
Rack spacing	1U chassis fits 3 CPU sleds
Weight	1 lb

Included Accessories

Support and maintenance	One year of ASM
Power cord	19 V, 65 W wall-mount AC/DC power adapter

Optional Accessories

SAVI 1U Chassis	SEN-01 can hold up to 3 total sleds (SAVI Server/Backup Server/CPU Sled)
-----------------	--

Visit the [SAVI iQ store](#) to explore all of our branded products!