



IP64-rated **QoraLux Accent 4"** is an elegant lighting solution for both interior and exterior applications. This compact unit enhances any space with ambient or directional lighting with rich RGB color mixing and 3267 K tunable white.

KEY BENEFITS

- Simplified installation with Class 2 low-voltage wiring
- Create vibrant lightscapes with RGB color mixing and 3267 K tunable white
- IP64-rated and suitable for interior or exterior installations
- Compounded energy-efficient savings with low-voltage power distribution
- Reduced failure rate with driverless fixtures
- Compatible with all QoraLux drivers
- 4.72 in with 9.8 W max power

SPECIFICATIONS

Control, Monitoring, and Network	
Control	DMX 512 (when using QoraLux driver)
DMX modes	2 modes of operation with driver


Lighting	
Color temperature	Tunable white, 3267 K
CRI (tunable white)	84.3
Each LED wattage	1.4 W
LED quantity	7
LED type	SMD 5050 R, G, B, TW
Lens angle	27°, without diffuser
Lumen	363 @full

Electrical	
Connection	RJ45 in and out
Drive method	Constant voltage
Power input	24 VDC
Total max power	9.8 W

Mechanical/Environmental	
Cable length	6 in
Dimensions	4.72 in x 4.72 in x 9.75 in (HxWxD)
Fastening system	Mounting bracket
Housing	Aluminum
IP rating	IP64
Operating temperature	-22 to 122 °F (-30 to 50 °C)
Weight	2.2 lb

Compatible Products*	
Single Output Driver	QD1-96-01
Triple Output DIN Driver	QD3-288-01
Twenty-Four Output Driver	QD24-480-01
Quad Output Driver	QD4-384-01

*Visit the [SAVI store](#) to view all of SAVI's branded products.



CONNECTIONS EXAMPLE

