

QFVS-94-01



The **QoraLux Flex Strip Vertical Stealth** can transform any venue or themed environment. The IP66-rated stealth strip offers 504 LEDs delivering impressive lighting effects with RGB color mixing and tunable white options. Available in 19' 10.5" reels with flexible and durable silicone casing, the Flex Strip Vertical Stealth's curve angle allows for easy concave and convex applications.

KEY BENEFITS

- · Simplified installation with Class 2 low-voltage wiring, flexible silicone casing, and horizontal curve angle
- Create pristine illumination with RGB color mixing and 2464 K tunable white
- · Designed to disappear into a black background when turned off
- IP66-rated and suitable for interior or exterior installations
- Included mounting clips and screws provide clean and seamless mounting
- Easily cut or link strips to achieve the desired length for each project
- Compounded energy-efficient savings with low-voltage power distribution
- · Reduced failure rate with driverless fixtures
- Compatible with all QoraLux drivers
- 19 ft 10.5 in with 94 W max power

SPECIFICATIONS

Control, Monitoring, and Network	
Control	DMX 512 (when using QoraLux driver)
DMX modes	4 channel mode: R, G, B, TW 7 channel mode: Dimmer, R, G, B, TW, strobe, macro

Lighting	
Color temperature	Tunable white, 2464 K
CRI (tunable white)	80
Curving type	Up and down curve when light output is facing up
Each LED wattage	0.19 W
LED quantity	504

hellosavi.com



QFVS-94-01

Lighting	
LED spacing	0.46 in
LED type	SMD 5050 R, G, B, TW

Electrical	
Connection	5 conductor cable
Drive method	Constant voltage
Power input	24 VDC
Total max power	94 W

Mechanical/Environmental	
Cuttable	Every 3.92 in, mark located on the bottom
Dimensions	19 ft 10.5 in x 19 mm x 19 mm (HxWxD)
Fastening system	Mounting clips, included
Housing	Silicone-type material, 3 type
Housing type	Flat top
IP rating	IP66
Length	19 ft 10.5 in, cable included
Operating temperature	-22 to 122 °F (-30 to 50 °C)
Weight	4 lb

Included Accessories	
Mounting clips (6)	

Optional Accessories	
1M Flex Strip Vertical Extrusion	QVFS-ACC-EXT
5M Flex Strip Vertical Flexible Mounting Channel	QVFS-ACC-FLE
Flex Strip Horizontal Left-Angle Cap	QHF-ACC-CAP-L
Flex Strip Horizontal Right-Angle Cap	QHF-ACC-CAP-R
Flex Strip Vertical End Cap	QVFS-ACC-CAP




OFVS-94-01


Optional Accessories	
Flex Strip Vertical End Cap with Cable Hole	QVFS-ACC-CAP-C
Flex Strip Vertical Left-Angle Cap	QVFS-ACC-CAP-L
Flex Strip Vertical Right-Angle Cap	QVFS-ACC-CAP-R
Flex Strip Vertical Single Point Mounting Clip	QVFS-ACC-SIN


Compatible Products*	
Single Output Driver	QD1-96-01
Triple Output DIN Driver	QD3-288-01
Quad Output Driver	QD4-384-01

^{*}Visit the <u>SAVI store</u> to view all of SAVI's branded products.

Tube With End Cap







19' Feet 10.5" Inches (Including Cable) / 19' Feet 9.25" (Without Cable)

QFVS-94-01

CONNECTIONS EXAMPLE

