



SAVI STREAM.One 4K delivers next-generation video distribution providing H.265 encoding at up to 4K30 – all over a single network cable to each display. Combining Canvas Video Wall with Canvas Sync, the **STREAM.One 4K** synchronizes a source over multiple displays creating a unified viewing experience while eliminating the cost and complexity of video wall design and installation.

KEY BENEFITS

- Featuring a web-based, user-friendly interface, configuration is quick and intuitive with SAVI Creator
- Automatic device discovery streamlines system integration
- HDMI pass-through eliminates the need for an external splitter and multiple HDMI connections
- Delivers a 4K stream and a parallel secondary stream up to 1080p
- HDMI input encodes audio and video signals into separate H.265 and H.264 streams as well as PCM audio
- Phoenix terminal block provides de-embedded unbalanced audio
- Motion JPEG enables a live preview of active sources directly in Creator and in Facility View
- PoE for clean wiring in every rack and remote power cycle
- Front screen and status LEDs provide at-a-glance information, troubleshooting, and quick configuration
- Custom splash screen image auto displays should the video signal drop, eliminating the “no signal” message

SPECIFICATIONS

Audio	
Encoding	PCM audio
Delay	0 – 1500 ms delay for analog audio
Sample frequency	44.1 kHz or 48 kHz
Stream	RTSP multicast

Video	
Bitrate	32 – 32000 kbit/s
Bitrate control	CBR or VBR
EDID selection	Large EDID table with file upload options for expansion
Frame rate options	5 – 30 FPS
Group of pictures options	5 – 300 GOP
Streams	RTP TS multicast, RTSP unicast, RTSP multicast

SPECIFICATIONS CONT.

Video (H.265)

Encoding resolution	Same as input, 3840 x 2160, 1920x1080, 1280x720, 640x480
H.265 level	Main

Video (H.264)

Encoding resolution	Same as input, 1920x1080, 1280x720, 640x480
H.264 level	Baseline, main, high

Electrical

PoE	802.3af 15.4 W
Power consumption	12 W
Requirements	12 V 1 A

Control, Monitoring, and Network

Network connectivity	10/100/1000 Mbps ethernet
LAN port	8pin RJ45 port with status LEDs

Inputs

HDMI input	1
------------	---

Outputs

Analog audio	Unbalanced Phoenix terminal block providing de-embedded audio
HDMI pass-through	1
Splash screen	Custom splash screen image when video signal drops, thus eliminating "no signal" from showing on displays
Stream out	6 video and 1 audio output stream per unit

SPECIFICATIONS CONT.

Mechanical/Environmental

Dimensions	1.35 in x 3.75 in x 8.50 in (HxWxD)
Mounting	Fits into one slot of our 4-slot chassis (SSC-01)
Operating temperature	32 to 140 °F (0 to 60 °C)
Storage temperature	4 to 194 °F (-20 to 90 °C)
Rack spacing	1U
Weight	1.53 lb

Included Accessories

Mounting	Screw taps for a secure fit (2)
Power Cord	100-240 VAC to 12 VDC adapter

Optional Accessories

1U chassis	STREAM.One Chassis (SSC-01)
------------	-----------------------------