



Whether it's 24/7 remote support software or interactive graphics capabilities, the CPU Sled comes preloaded with Windows 11 Pro, ensuring compatibility with various software packages. The highly versatile CPU Sled integrates seamlessly into a single slot of our 3-slot 1U chassis, offering sleek and industrial functionality.

## KEY BENEFITS

- Preloaded with Windows 11 Pro
- Over a decade of proven performance, power, and reliability
- Versatile and customizable for music, digital signage, remote monitoring, and more
- Fits into a single slot of our modular, 3-slot 1U chassis with space for two additional processors, e.g., **SAVI Server Pro**, Backup Server, or lighting control
- Front panel power reset button for easy access
- Includes the first year of Annual Support and Maintenance (ASM)
- 

## SPECIFICATIONS

### Control, Monitoring, and Network

Control	Ethernet connection, (2) USB 3.0, (1) USB-C
---------	---

Network connectivity	10/100/1000 Mbps ethernet
----------------------	---------------------------

LAN port	8-pin RJ45 port with status LEDs
----------	----------------------------------

Processor/CPU	Intel® Core™ i5-10210U Processor (6 M Cache, up to 4.20 GHz)
---------------	--

RAM	16 GB DDR4 RAM
-----	----------------

Storage	250 GB SSD
---------	------------

Supported operating systems	Windows 11 Pro
-----------------------------	----------------

### Electrical

Connection	Switching power supply AC/DC adapter, operation from 100 VAC +/-15% 2.1 mm power plug
------------	---

Power consumption	90 W
-------------------	------

Power input	100-240 V ~ 50/60 Hz input to include AC/DC power supply
-------------	--

## SPECIFICATIONS CONT.

**Mechanical/Environmental**

Dimensions	1.625 in x 4.75 in x 5.25 in (HxWxD)
Mounting	Fits into one slot of our 3-slot chassis, (2) screw taps for a secure fit
Operating temperature	32°–122°F (0°C–50°C)
Storage temperature	-40°–140°F (-40°–60°C)
Rack spacing	1RU chassis fits 3 CPU sleds
Weight	1 lb

**Included Accessories**

Power cord	19 V, 65 W wall-mount AC-DC power adapter
------------	---